

# RVC-300

Our upright coolers are a reference in the international market because of its quality, reliability and thanks to our collaboration with the most prestigious beverages brands in this range for over 30 years.

In efficold we have the possibility of branding in sides, doors, crystals ... All of them designed exclusively for our clients.



## Features

- Internal LED light vertically arranged to maximize the product visibility.
- Interior made of thermoformed plastic and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminum profile and handle either inlaid on the side.
- Four shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m<sup>3</sup>.
- Temperature control by analog thermostat.
- Two back rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Door with self-closing and opening fixation system.
- Automatic evaporation of defrost water.
- Low maintenance condenser.
- Palletized 1 unit per pallet.

## Options

- Exterior customizable.
- Printed and / or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Personalized price-tags.



Reliability



Hydrocarbons



Energy Saving



Customization

## Technical Data

External dimensions (mm)	620 x 690 x 2000
Net weight (kg)	91
Internal net volume (Lt)	400
Capacity 33 cl cans / 50 cl pets (pcs)	518 / 250
24h energy consumption (kW/h)	2,55
Climatic class	CC2-K4 (32°C/65%HR)

\* (width x depth x height)

Temperature range (°C)	+1 / +9
Refrigerant	R-600a
Voltage / frequency	230v / 50Hz
Canopy serigraphy dimensions (mm)	613 x 177
Lateral serigraphy dimensions (mm)	590 x 1988
Transport 40' container / 13m truck	51 / 60