

# RV-235

Offering high reliability and including all the new technologies developed by our R&D&i teams, our counter top coolers are designed while taking into account the current limitations of space and the needs of large branding areas.

A product that will attract the attention of any buyer thanks to its stylized design, customization and fantastic illumination.



## Features

- Interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminium profile and handle either inlaid on the side.
- Five shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m<sup>3</sup>.
- Temperature control by analog thermostat.
- Two rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Low-maintenance condenser.
- Unitary palletized.

## Options

- Exterior customizable
- Printed and /or illuminated logo in the glass.
- *Energy Management Device (EMD)*.
- *Door lock*.
- *Personalized price-tags*.



Reliability



Hydrocarbons



Energy Saving



Customization

## Technical Data

External dimensions (mm)	483 x 673 x 1669
Net weight (kg)	80
Internal net volume (Lt)	208
Capacity 33 cl cans / pet 50cl (pcs)	252 / 150
24h energy consumption (kW/h)	2,37
Climatic class	CC2 (32°C/65%HR)

\* (width x depth x height)

Temperature range (°C)	+2 / +6,6
Refrigerant	R-600a
Voltage / frequency	230v / 50Hz
Glass serigraphy dimensions (mm)	379 x 1248
Lateral serigraphy dimensions (mm)	586 x 1640
Transport 40' container / 13m truck	66 / 75