

RV-800

Our upright coolers are a reference in the international market because of its quality, reliability and thanks to our collaboration with the most prestigious beverages brands in this range for over 30 years.



Reliability



Hydrocarbons



Energy Saving



Customization

In efficold we have the possibility of branding in sides, doors, crystals ... All of them designed exclusively for our clients.

Features

- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glazed door mounted on an aluminum profile and handle in the front.
- Five shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Two rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Doors with self-closing system.
- Low-maintenance condenser.
- Unitary palletized.

Options

- Exterior and canopy customizable.
- Printed logo in the glass.
- Energy Management Device (EMD).
- Door lock.

Technical Data

External dimensions (mm)	875 x 690 x 1735
Net weight (kg)	126
Internal net volume (Lt)	598
Capacity 33 cl cans / 50 cl pets (pcs)	816 / 408
24h energy consumption (kW/h)	4,51
Climatic class	CC1 (25°C/60%HR)

* (width x depth x height)

Temperature range (°C)	+2 / +10
Refrigerant	R-600a
Voltage / frequency	230v / 50Hz
Glass serigraphy dimensions (mm)	374 x 1598
Lateral serigraphy dimensions (mm)	575 x 1975
Transport 40' container / 13m truck	39 / 42