

RVC-700

Our upright coolers are a reference in the international market because of its quality, reliability and thanks to our collaboration with the most prestigious beverages brands in this range for over 30 years.



Reliability



Hydrocarbons



Energy Saving



Customization

Technical Data

External dimensions (mm)	785 x 797 x 2100
Net weight (kg)	155
Internal net volume (Lt)	600
Capacity 33 cl cans (pcs)	800
24h energy consumption (kW/h)	4,3
Climatic class	CC2 (32°C/65%HR)

* (width x depth x height)

In efficold we have the possibility of branding in sides, doors, crystals ... All of them designed exclusively for our clients.

Features

- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminium profile and handle either inlaid on the side.
- Five shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Four rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Unitary palletized.

Options

- Exterior and canopy customizable.
- Printed logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Personalized price tags.
- Door with self-closing system.

Temperature range (°C)	+2 / +10
Refrigerant	R-290
Voltage / frequency	230v / 50Hz
Canopy serigraphy dimensions (mm)	765 x 210
Lateral serigraphy dimensions (mm)	687 x 2073
Transport 40' container / 13m truck	42 / 48