RVC-1000



Our upright coolers are a reference in the international market because of its quality, reliability and thanks to our collaboration with the most prestigious beverages brands in this range for over 30 years.

In efficold we have the possibility of branding in sides, doors, crystals ... All of them designed exclusively for our clients.











Hvdrocarbons

Energy Saving

Features

- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robutness.
- Double glazed door mounted on an aluminum profile and handle in the front.
- Eight shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- o Temperature control by digital thermostat with automatic defrost.
- Six rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Doors with self-closing system.
- o Low-maintenance condenser.
- o Unitary palletized.

Options

- Exterior and canopy customizable.
- Printed logo in the glass.
- Energy Management Device (EMD).
- o Door lock.
- Personalized price tags.
- Available with R-600a or R-290 gas.

Technical Data

External dimensions (mm)	1250 x 725 x 2040
external difficultions (filliff)	1230 X 723 X 2040
Net weight (kg)	106
Internal net volume (Lt)	665
Capacity 33 cl cans / 50 cl pets (pcs)	960 / 480
24h energy consumption (kW/h)	4,53
Climatic class	CC2 (32°C/65%HR)

^{* (}width x depth x height)

Temperature range (°C)	0 / +6,6
Refrigerant	R-290
Voltage / frequency	230v / 50Hz
Canopy serigraphy dimensions (mm)	1223 x 190
Lateral serigraphy dimensions (mm)	2018 x 629
Transport 40' container / 13m truck	27 / 30