RVCS-1000

Our upright coolers are a reference in the international market because of its quality, reliability and thanks to our collaboration with the most prestigious beverages brands in this range for over 30 years.

In efficold we have the possibility of branding in sides, doors, crystals ... All of them designed exclusively for our clients.



Reliability | Hydrocarbons | Energy Saving | Customization

Features

- **Slide doors version**.
- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glazed door mounted on an aluminum profile.
- Eight shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Six rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Doors with self-closing system.
- Low-maintenance condenser.
- Unitary palletized.

Options

- Exterior and canopy customizable.
- Printed logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Personalized price tags.
- Available with R-600a or R-290 gas.

Technical Data

External dimensions (mm)	1250 x 715 x 2040
Net weight (kg)	166
Internal net volume (Lt)	665
Capacity 33 cl cans / 50 cl pets (pcs)	960 / 480
24h energy consumption (kW/h)	5,14
Climatic class	CC1 (25°C/60%HR)

Temperature range (°C)	0 / +6,6
Refrigerant	R-290
Voltage / frequency	230v / 50Hz
Canopy serigraphy dimensions (mm)	1170 x 190
Lateral serigraphy dimensions (mm)	2018 x 685
Transport 40' container / 13m truck	25 / 30

* (width x depth x height)

efficold reserves the right to modify the characteristics of its products without prior notice