

RVC-450

Our upright coolers are a reference in the international market because of its quality, reliability and thanks to our collaboration with the most prestigious beverages worldwide brands in this range for over 30 years.



Reliability



Hydrocarbons



Energy Saving



Customization

Our products have the best branding surface through the latest printing techniques. They also reduce their consumption by incorporating LED technology, hydrocarbons and double glazing.

Features

- Interior LED light vertically arranged to maximize the product visibility.
- Exterior made of metal sheet that provide a great robustness and interior in thermoformed plastic.
- Double glass door mounted on an aluminium profile and handle either inlaid on the side.
- Five shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Two rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Door with self-closing and opening fixation system.
- Low-maintenance condenser.
- Unitary palletized.

Options

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Personalized price-tags.

Technical Data

External dimensions (mm)	690 x 680 x 2025
Net weight (kg)	117
Internal net volume (Lt)	415
Capacity 33 cl cans / 50 cl pets (pcs)	580 / 240
24h energy consumption (kW/h)	4,17
Climatic class	CC1-K4 (25°C/60%HR)

* (width x depth x height)

Temperature range (°C)	+1 / +9
Refrigerant	R-600a
Voltage / frequency	230v / 50Hz
Fake canopy serigraphy dimensions (mm)	610 x 177
Lateral serigraphy dimensions (mm)	580 x 1987
Transport 40' container / 13m truck	48 / 54