RV-100



Offering high reliability and incluiding all the new technologies developed by our R&D&i teams, our counter top coolers are designed with the current limitations of space in most of the establishments.

A product that will attract the attention of any buyer thanks to its stylized design, customization and fantastic illumination.









Reliability Hydrocarbons

Energy Saving



ving Customization

Features

- $\circ~$ Internal LED light vertically arranged to maximize the product visibility.
- Exterior made of metal sheet that provide a great robustness and interior made of thermoformed plastic.
- Double glass door mounted on a plastic profile and handle either inlaid on the side.
- One shelf included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by analog thermostat.
- Four feets adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Low-maintenance condenser.
- Palletized four units per pallet.

Options

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Personalized price-tags.
- Door with self-closing system.
- Door with aluminium profile.

Technical Data

External dimensions (mm)	445 x 480 x 700
Net weight (kg)	35
Internal net volume (Lt)	56
Capacity 33 cl cans / 50 cl pets (pcs)	60 / 25
24h energy consumption (kW/h)	1,42
Climatic class	CC2-K4 (32°C/65%HR)
* (width x depth x height)	

Temperature range (°C)	+1/+9
Refrigerant	R-600a
Voltage / frequency	230v / 50Hz
Glass serigraphy dimensions (mm)	380 x 535
Lateral serigraphy dimensions (mm)	418 x 679
Transport 40' container / 13m truck	192 / 224