

# RVC-280

Our upright coolers are a reference in the international market because of its quality, reliability and thanks to our collaboration with the most prestigious beverages worldwide brands in this range for over 30 years.



Reliability



Hydrocarbons



Energy Saving



Customization

Our products have the best branding surface through the latest printing techniques. They also reduce their consumption by incorporating LED technology, hydrocarbons and double glazing.

## Features

- Interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminium profile and handle in the front.
- Five shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m<sup>3</sup>.
- Temperature control by digital thermostat with automatic defrost.
- Two rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Door with self-closing and opening fixation system.
- Low-maintenance condenser.
- Unitary palletized.

## Options

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.

## Technical Data

|                                        |                     |
|----------------------------------------|---------------------|
| External dimensions (mm)               | 600 x 690 x 2000    |
| Net weight (kg)                        | 101                 |
| Internal net volume (Lt)               | 390                 |
| Capacity 33 cl cans / 50 cl pets (pcs) | 525 / 261           |
| 24h energy consumption (kW/h)          | 4,17                |
| Climatic class                         | CC1-K4 (25°C/60%HR) |

\* (width x depth x height)

|                                     |             |
|-------------------------------------|-------------|
| Temperature range (°C)              | +1 / +9     |
| Refrigerant                         | R-600a      |
| Voltage / frequency                 | 230v / 50Hz |
| Canopy serigraphy dimensions (mm)   | 592 x 264   |
| Lateral serigraphy dimensions (mm)  | 575 x 1975  |
| Transport 40' container / 13m truck | 53 / 63     |