

# Slim Cooler

The **Slim Cooler** is the most complete merchandising tool for an impulse purchase. Thanks to its **compact dimensions**, they make it easily **located in any area with reduced space**.

Our Slims stand out for **their personalized design with the needs of each customer**. We make our customers' products stand out from the rest at the point of sale.

## Features

- **The perfect choice for points of sale with heavy traffic of people.**
  - **Double LED** interior light arranged vertically to maximize product visibility.
  - Interior and exterior made of metal sheet that provides a **great robustness**.
  - Door with double glazing, aluminum profile and plastic handle embedded in the same color.
  - **Uniform cold distribution inside** thanks to the excellent cooling system design.
  - Provision of five series shelves.
  - Leveling feet in the front and rollers in the rear.
  - Ecological injected polyurethane insulation free of CFCs, density 40kg/m<sup>3</sup>.
  - Temperature control by **digital thermostat with automatic defrost**.
  - Door with self-closing and opening fixation system.
  - Unitary palletizing.

## Options

- Customizable exterior finished with stainless steel, wood, plastic...
- Lock to prevent opening.
- Custom price holder.
- Energy Management Device (EMD).
- Canopy printed and illuminated.
- Greater endowment of shelves.
- Customizable handle.
- Door with Prime full-glass finish.
- APP to change the color of LEDs in real time.
- Intelligent thermostat "efficold IoT", with alarm option, geolocation, remote management...



Reliability



Hydrocarbons



Energy Saving



Customization

## Technical Data

External dimensions (mm)	360 x 390 x 1871
Net weight (kg)	63
Internal net volume (Lt)	100
Capacity 33 cl cans / 50 cl pets (pcs)	104 / 56
24h energy consumption (kW/h)	2,13

Refrigerant	R-600a
Voltage	230v
Frequency	50Hz
Canopy serigraphy dimensions (mm)	315 x 142
Lateral serigraphy dimensions (mm)	315 x 1843

Climatic class

CC2-K4 (32°C/65%HR)

Transport 40' container / 13m truck (6 uds)

144 / 198

Temperature range (°C)

+1 / +9

Transport 40' container / 13m truck (1 ud)

76 / 92

\* (width x depth x height)

