

# EFBBC-5 2P

Our refrigerated wall displays are a reference in the international market for their quality and reliability, thanks to our collaboration with the most prestigious beverage brands in this range for over 30 years.

Refrigerated wall displays are specially designed for small spaces, and stand out for their low energy consumption and low noise level.

## Features

- Four flat shelves included as standard.
- Four height-adjustable legs.
- Digital thermostat and automatic defrost.
- Automatic evaporation of defrost water.
- Low-maintenance condenser.
- Dual internal LED lighting.
- Eco-friendly injected polyurethane insulation, CFC-free, density 40kg/m<sup>3</sup>.
- Ultra-low energy consumption.
- Low noise level of 53dB(A).
- Door self-closing system for perfect sealing at all times.
- The door remains open at 90° to facilitate loading.
- Eco thermostat with learning mode.
- Interior in gray color and exterior in black steel sheet providing great robustness.



## Options

- Customizable interior and exterior color.
- Reversible door.
- Door lock.



Reliability



Hydrocarbons



Energy Saving



Customization

## Technical Data

Exterior dimensions (mm)	1435 x 512 x 850
Net weight (kg)	77
Internal volume (L)	264
Capacity for 33cl cans (qty)	350
Energy consumption (kWh/24h)	0.47
Climatic class	CC2-K2 (32°C / 65% HR)

\* (width x depth x height)

Temperature range (°C)	-1 / + 6
Refrigerant	R-600a
Voltaje / frequency	230v / 50Hz
Refrigerating power (W)	293
Noise level (dBA)	53
Transport truck 13m (qty)	66