

EERM-250

Our upright coolers are a reference in the international market because of its quality, reliability and thanks to our collaboration with the most prestigious beverages brands in this range for over 30 years.

In **efficold** we have the possibility of branding in sides, glass doors... All of them designed exclusively for our clients.

Features

- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass doors mounted on a plastic profile and handle in the front.
- Two shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Four feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Door lock as standard.
- Low-maintenance condenser.
- Unitary palletized.

Options

- Exterior customizable.
- Printed logo in the glass.
- Energy Management Device (EMD).



Reliability



Hydrocarbons



Energy Saving



Customization

Technical Data

External dimensions (mm)	920 x 570 x 900
Net weight (kg)	80
Internal net volume (Lt)	218
Capacity 33 cl cans / PET 500ml (pcs)	228 / 132
24h energy consumption (kW/h)	2,76
Climatic class	CC2-K4 (32°C/65%HR)
Temperature range (°C)	+2 / +8

* (width x depth x height)

Refrigerant	R-600a
Voltage	230v
Frequency	50Hz
Lateral serigraphy dimensions (mm)	460 x 855
Glass serigraphy dimensions (mm)	370 x 718
Transport 40' container / 13m truck	76 / 96