SZ-345

Our upright coolers are a reference in the international market because of its quality, reliability and thanks to our collaboration with the most prestigious beverages brands in this range for over 30 years.

In efficold we have the possibility of branding in sides, doors, crystals ... All of them designed exclusively for our clients.



Reliability | Hydrocarbons | Energy Saving | Customization

Features

- Double internal LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Glass door mounted on an aluminium profile and handle either inlaid on the side.
- Five shelves included. – Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Two rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Door with self-closing system.
- Unitary palletized.

Options

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.

Technical Data

External dimensions (mm)	500 x 615 x 1985
Net weight (kg)	82
Internal net volume (Lt)	345
Capacity 33cl cans (pcs)	380
24h energy consumption (kW/h)	3,31
Climatic class	CC2 (32°C/65%HR)

Temperature range (°C)	-3,5 / -1
Refrigerant	R-290
Voltage / frequency	230v / 50Hz
Lateral serigraphy dimensions (mm)	557 x 1946
Glass serigraphy dimensions (mm)	423 x 1582
Transport 40' container / 13m truck	66 / 75

* (width x depth x height)

efficold reserves the right to modify the characteristics of its products without prior notice